

Typical Specification:

Provide, where indicated, a flexible connector consisting of stainless steel hose surrounded and supported by wire braid. End fittings are to be CS female swivel with a male NPT adapter x CS fixed male NPT. Connector to be _____ inches nominal pipe size by _____ inches overall length; **Thermo Tech model FFCHS DOM or equal**.

NOMINAL PIPE SIZE	BEND RADIUS	WORKING PRESSURE PSIG	AVAILABLE LENGTH ISSUES			
1/2"	5.5"	995	12	18	24	36
3/4"	6.5"	755	12	18	24	36
1"	7.5"	605	12	18	24	36
1 1/4"	10.5"	575		18	24	36
1 1/2"	11.5"	525		18	24	36
2"	12.5"	455		18	24	36
Job Contractor Engineer Representative Order No Date Submitted by						
Approved by Date						
Tag						
1						

Notes:

Maximum Operating Temperature: 850°F

Flexible Stainless Steel Braided Hose Assembly

Designed for Industrial or HVAC piping systems; Suitable for vacuum Use

These quality S/S flexible hoses are nonflammable

Special end fittings, sizes, tube material and pressure ratings available

These are Domestic hoses, manufactured with pride in Denver, Colorado, USA



287 South Sante Fe Drive Denver, Colorado 80223 Phone (303) 698-9988 www.thermotechdenver.com

Flexible Connector Type FF/CHS DOM