



Available with Stainless Steel Sanitary
Clamp End fittings as Shown
Or:
Stainless Steel Bevel Seat and Hex Nut
Or:
Stainless Steel O.D. Tube Size Weld Ends
Or:
Stainless Steel Cam Lock Quick Connects
Or:
Stainless Steel Flanged or Thread Ends

Fabricated in Lengths to 100 Feet

General Notes:

The hose and fittings meet or exceed **USDA, FDA, and 3A-Class 3** Sanitary Standards.

The hose assemblies are available to match **1 1/2", 2", 2 1/2", 3", 4"** sanitary end fittings.

Working Pressure: **150 PSIG**
Maximum Temperature: **225° F Constant, 250° F Intermittent.**

Smooth sanitary interior surface has **no area of entrapment** between the hose and fittings.

Hose and fittings are suitable for **Clean In Place** with hot caustic or open end steam cleaning.

MODEL 7390 - 2856			
SANITARY TRANSFER HOSE			
<i>typical detail</i>			
DRAWN	CHECKED	APPROVED	DATE

Nominal Hose Size	Minimum Bend Radius
1 1/2"	6.0"
2"	9.0"
2 1/2"	12.0"
3"	15.0"
4"	21.0"

**THERMO
TECH INC.**

287 South Santa Fe Drive
Denver, Colorado 80223
Phone: (303) 698-9988
Fax: (303) 698-2184

Wire reinforced for **full suction and discharge** hose applications.