




# Flexible Connector

Type: FFN/GAS Male NPT  
FFW/GAS Weld Ends

SUBMITTAL

CSA / AGA Approved Gas Connectors  
Capable of 2" of Lateral Offset For  
Seismic or HVAC Piping Applications

Job _____	
Contractor _____	
Engineer _____	
Representative _____	
Order No. _____	Date _____
Submitted by _____	
Approved by _____	Date _____
Tag _____	



Nominal Pipe Size	Overall Length	Working Pressure
1/2"	17"	150 PSIG
3/4"	18 1/2"	150 PSIG
1"	19 1/2"	150 PSIG
1 1/4"	19 1/2"	150 PSIG
1 1/2"	20"	150 PSIG
2"	21"	150 PSIG
2 1/2"	22 1/2"	150 PSIG
3"	25 1/2"	150 PSIG
4"	30 1/2"	150 PSIG

**Notes:**

Maximum Working Pressure  
Based on Non-Shock Service

Stainless Steel Corrugated  
Braided Hose Construction

Not Designed for Extension  
or Compression Applications

Install Without Torque, Sharp  
Bends or Excessive Offset

Available With C/S Sch 40 Male  
NPT or Butt Weld End Fittings

**THERMO  
TECH INC.**

287 South Santa Fe Drive  
Denver CO 80223  
Phone 303 698 9988  
Fax 303 698 2184  
[www.ThermoTechDenver.com](http://www.ThermoTechDenver.com)