



GENERAL NOTES

ACCEPTED BY THE **USDA MEAT AND POULTRY AND DAIRY STANDARDIZATION SECTIONS.**

HOSE AND FITTINGS MEET OR EXCEED **FDA AND 3A SANITARY STANDARDS.**

AVAILABLE TO MATCH **1½, 2, 2½, 3, 4" DIAMETER TUBING OR FITTINGS.**

WORKING PRESSURE **250 PSIG**
 MAXIMUM TEMPERATURE TO **230°F.**

SMOOTH, SANITARY INTERIOR SURFACE. **NO AREA OF ENTRAPMENT** BETWEEN HOSE AND FITTINGS.

SUITABLE FOR **CLEAN IN PLACE** WITH HOT CAUSTIC AND OPEN END STEAM.

AVAILABLE WITH **STAINLESS STEEL SANITARY CLAMP END FITTINGS AS SHOWN**

- OR: **STAINLESS STEEL BEVEL SEAT AND HEX NUT**
- OR: **STAINLESS STEEL TUBE SIZE BUTT WELD ENDS**
- OR: **STAINLESS STEEL CAM TYPE QUICK CONNECTS**
- OR: **STAINLESS STEEL FLANGE OR THREAD ENDS**

MANUFACTURED IN LENGTHS TO 100 FEET

NOMINAL SIZE (INCHES)	MINIMUM BEND RADIUS (INCHES)
1½	5
2	6
2½	12
3	18
4	36

REINFORCED FOR **FULL SUCTION AND DISCHARGE APPLICATIONS.**

THIS HOSE SPRINGS BACK WHEN CRUSHED.

<i>THERMO</i>		287 South Santa Fe Drive Denver, CO 80223 Phone (303) 698-9988 Fax (303) 698-2184	
<i>TECH</i> INC.			
MODEL 3063 SANITRON TRANSFER HOSE typical detail FULL VACUUM-HIGH PRESSURE-CRUSH RESISTANT			
DRAWN	CHECKED	APPROVED	DATE
			DRAWING NUMBER